

From: [Debra M. Butchart](#)
To: [BR](#)
Subject: Bridge Advertisement (DSI 24-053) Polyester Polymer Minimum Thickness
Date: Tuesday, January 28, 2025 1:27:55 PM

The [EPG](#) has been updated as described below:

Implementation Statement: **Effective immediately for details not started.**

(The Implementation Statement is a recommendation by the Development Section. The SPM is responsible for the level of implementation for any particular job.)

Revision Date	Items Revised	Description of Change
Jan. 2025	EPG: 751.1.3.6	The minimum allowable thickness for polyester polymer concrete (PPC) is increased from 3/4 inch to 1 inch. It is critical that PPC is at least 3/4 inch for acceptable performance. Specifying 1 inch on the plans will help to ensure that not less than 3/4 inch is applied in the field.
	Bridge Standard Drawings: NA	
	MicroStation Cells: NA	
	Std. Specifications: NA	
	Standard Plans: NA	
	Bridge Special Provisions: NA	

Follow links above for more information, or to view more details about this (or any) revision, use the [Revision Index Database](#), located under Completed Revisions on Development's Sharepoint page.

Instructions:

Under Tables (left-hand side) double-click on RevisionRecords.

Click on the link under the Effective Date to access documentation for the completed revision.

Debra (Debbie) Butchart
(formerly Debra Beckwith)
Structural Specialist
Development Section
Bridge Division
MoDOT- 105 West Capitol Ave
573-522-8718