

**From:** [Debra M. Butchart](#)  
**To:** [BR](#)  
**Subject:** Bridge Advertisement (DSI 24-048) Bridge Barrier and Railing Selection  
**Date:** Friday, January 31, 2025 8:36:32 AM

---

The [EPG](#) has been updated as described below:

**Implementation Statement:** Effective immediately for design process not started.

*(The Implementation Statement is a recommendation by the Development Section. The SPM is responsible for the level of implementation for any particular job.)*

Revision Date	Items Revised	Description of Change
<a href="#">Jan. 2025</a>	EPG: <a href="#">751.1.3.4</a> ; <a href="#">751.12.1</a>	EPG 751.1.3.4 – Simplified guidance for barrier and railing selection in rehab projects. <ul style="list-style-type: none"><li>• Removed AADT and speed limit from selection criteria.</li><li>• Removed roadway width criteria from the exceptions list to MASH TL-4 barriers or railings.</li><li>• Added exception criteria for bridge with non-mountable sidewalks.</li><li>• Thrie beam shall not be used for redecks.</li><li>• Fence attachments to single-sloped concrete barriers reduce the TL rating to MASH TL-3 max.</li></ul>
	Bridge Standard Drawings: NA	
	MicroStation Cells: NA	
	Std. Specifications: NA	
	Standard Plans: NA	
	Bridge Special Provisions: NA	
	EPG 751.12 – Guidance is updated to sync with changes in EPG 751.1.3.4. Includes guidance for fence attachments and bridges with non-mountable sidewalks. Tweaked some language for two tube rail.	

Follow links above for more information (internal only).

Debra (Debbie) Butchart  
(formerly Debra Beckwith)  
Structural Specialist  
Development Section  
Bridge Division  
MoDOT- 105 West Capitol Ave  
573-522-8718